

4F Fiber Optic Indoor Termination Box

4 Fiber Splice Capacity, 4 Patch Ports

ITB-210140-4SC-4S-4P is a compact fiber terminal for use at the final fiber termination point in the customer premises.

The ITB-210140-4SC-4S-4P provides mechanical protection and managed fiber control in an attractive format suitable for use inside customer premises.

A variety of possible fiber termination techniques are accommodated.

Features

- Ergonomically & compact design
- Bottom cable entry with Sideway front door
- Indoor use for small and large business premises
- Easy re-entry with a minimum of tools, time and cost
- Up to 4 cores (heat shrink) or 2 cores (3M mechanical splices)
- Can hold 4 SC simplex adaptors
- Can be used for uncut cable loop
- Reusable, UV resistant and weather proof
- ROHS compliance

Specifications

Model No.	TKS-FOM-36 ITB-210140-4SC-4S-4P
Capacity	4 splices / 4 SC-SX
Splitter Capacity	PLC 1x 1/4
Cable Ports	1 cable port - max \varnothing 8mm
Drop Cable	4 drop cable ports - max \varnothing 3mm
Size H x L x W	210mm x 140mm x 40mm
Application	Wall mounted



12F Indoor Termination Box

12 Fiber Splice Capacity, 12 Patch Ports

ITB-258207-12SC-12S-12P is a compact fiber terminal for use at the final fiber termination point in the customer premises.

The ITB-258207-12SC-12S-12P provides mechanical protection and managed fiber control in an attractive format suitable for use inside customer premises.

A variety of possible fiber termination techniques are accommodated.

Features

- 2 main ports is for 1 loop cable
- or 2 cables with max Ø 15 or Ø 12 mm.
- The reserved port is for cables with max Ø 15mm
- The 12 small ports ,each port can hold 1 drop cable
- Bending radius > 30mm
- Designed for Wall and Pole mount applications with Safety lock
- Reusable, UV resistant, rugged and durable
- Designed for small and medium volumes of fiber optic cables
- ROHS compliance

Specifications

Model No.	TKS-FOM-26 ITB-258207-12SC-12S-12P
Capacity	12 splices / 12 SC-SX
Splitter Capacity	PLC 1x 1/8
Cable Ports	2 cable ports - max Ø 12mm
Drop Cable	12 drop cable ports - max Ø 3mm
Size H x L x W	258mm x 207mm x 64mm
Application	Wall mounted

