


Indoor 4 WAY TAP (unbalance)

ITEM	FREQUENCY RANGE	SPECIFICATION
Insertion loss	5 ~ 1000 MHz	12.5 ± 1.5 dB
(IN - TAP1)	1000 ~ 1218 MHz	12.5 ± 1.5 dB
Insertion loss	5 ~ 1000 MHz	13.5 ± 1.5 dB
(IN - TAP2)	1000 ~ 1218 MHz	13.5 ± 1.5 dB
Insertion loss	5 ~ 1000 MHz	14.5 ± 1.5 dB
(IN - TAP3)	1000 ~ 1218 MHz	14.5 ± 1.5 dB
Insertion loss	5 ~ 1000 MHz	15.5 ± 1.5 dB
(IN - TAP4)	1000 ~ 1218 MHz	15.5 ± 1.5 dB
	5 ~ 15 MHz	> 33 dB
	15 ~ 40 MHz	> 33 dB
Isolation	40 ~ 470 MHz	> 33 dB
(TAP - TAP)	470 ~ 862 MHz	> 30 dB
	862 ~ 1000 MHz	> 30 dB
	1000 ~ 1218 MHz	> 27 dB
	5 ~ 15 MHz	16 dB
	15 ~ 40 MHz	16 dB
Return loss	40 ~ 470 MHz	16 dB
(IN/TAP)	470 ~ 862 MHz	16 dB
	862 ~ 1000 MHz	16 dB
	1000 ~ 1218 MHz	16 dB