

SWINGING DRAWER 3HU, 19" / ETSI RACK TYPE, FO SPLICE & PATCH PANEL



Design and Properties

- 3HU 144F capacity with SC types DX adapters
- 19" and ETSI Compatible
- Magnetic locking system
- Light gray RAL 7035 or Black RAL 9005 electrostatic powder coating
- Other adapter types may be available upon request (ST, FC, E2000 etc.)
- Complies Bellcore GR- 326 standarts
- 12F / 24F (Double stack) capacity per splice cassette
- Cable entry is allowed from each side acc. to the system design
- Provides management of fibres through Splicing and Patching.
- 30 mm.min.Fiber bending radius is controlled
- Available for max. 8 cassettes

Dimension(s)

H : 133,5 mm (3HU)
W : 482,6 mm (19")
D : 300,0 mm

Standart Kit Contents

- Optional SC DX adapters acc. to the capacity
- Standart Splice Trays with Focabex logo acc. to the capacity
- Optional SC Pigtaills for selected type and capacity
- Optional Single fiber Splice Protector Sleeves
- ETSI Mounting Brackets upon request.
- Standart Cable Fixing / Guiding / Routing components, Cable glands and Transporting Corrugated plastic tube
- Standart Focabex and Laser symbol stickers on front panel

Complies with

- Optical: Tested at 850nm, 1310nm and 1550nm
- Dry heat: BS EN 60068-2-2 Test Bb
- Damp heat: IEC 60068-2-3: 1969
- Change of temperature: IEC 60068-2-14: 1984
- Vibration: IEC 60068-2-6: 1995
- Shock: IEC 60068-2-27: 1987
- Storage and Transportation temp.(°C) :-40 to +80
- Operation temp.(°C):0 to +50