

## Indoor 8 WAY TAP



### 1. Descriptions

8WITB\*\*dB 1.2 series 8way tap, with maximum operating frequency up to 1.2GHz and zinc alloy integrated housing, it has excellent EMC indicators.

### 2. Features

- Full SMT production process.
- Zinc alloy integrated housing, Plated Nickel
- Center conductor is Beryllium Copper Plated Gold.
- Low insertion loss, high isolation.

### 3. Specifications

ITEM	FREQUENCY RANGE	SPECIFICATION		
		8WITB14dB 1.2	8WITB16dB 1.2	8WITB20dB 1.2
Insertion loss (IN - OUT)	5 ~ 15 MHz	7.5 ± 1.0 dB	6.8 ± 1.0 dB	5.6 ± 1.0 dB
	15 ~ 40 MHz	7.5 ± 1.0 dB	6.8 ± 1.0 dB	5.6 ± 1.0 dB
	40 ~ 470 MHz	7.5 ± 1.0 dB	6.8 ± 1.0 dB	5.6 ± 1.0 dB
	470 ~ 862 MHz	7.5 ± 1.0 dB	6.8 ± 1.0 dB	5.6 ± 1.0 dB
	862 ~ 1000 MHz	7.5 ± 1.0 dB	6.8 ± 1.0 dB	6.0 ± 1.0 dB
	1000 ~ 1218 MHz	8.5 ± 1.0 dB	7.8 ± 1.0 dB	6.5 ± 1.0 dB
Insertion loss (IN - TAP)	5 ~ 1000 MHz	14.3 ± 1.5 dB	16.0 ± 1.5 dB	20.0 ± 1.5 dB
	1000 ~ 1218 MHz	14.5 ± 1.5 dB	16.0 ± 1.5 dB	20.0 ± 1.5 dB
Isolation (OUT - TAP1/2/3/4)	5 ~ 15 MHz	> 30 dB	> 30 dB	> 30 dB
	15 ~ 40 MHz	> 30 dB	> 30 dB	> 30 dB
	40 ~ 470 MHz	> 22 dB	> 25 dB	> 28 dB
	470 ~ 862 MHz	> 22 dB	> 22 dB	> 25 dB
	862 ~ 1000 MHz	> 22 dB	> 22 dB	> 25 dB
	1000 ~ 1218 MHz	> 20 dB	> 20 dB	> 23 dB

ITEM	FREQUENCY RANGE	SPECIFICAION		
		814	816	820
Isolation (TAP - TAP)	5 ~ 15 MHz	> 35 dB	> 35 dB	> 35 dB
	15 ~ 40 MHz	> 35 dB	> 35 dB	> 35 dB
	40 ~ 470 MHz	> 32 dB	> 33 dB	> 33 dB
	470 ~ 862 MHz	> 26 dB	> 30 dB	> 30 dB
	862 ~ 1000 MHz	> 26 dB	> 30 dB	> 30 dB
	1000 ~ 1218 MHz	> 26 dB	> 28 dB	> 30 dB
Return loss (IN/OUT/TAP)	5 ~ 15 MHz	16 dB		
	15 ~ 40 MHz	16 dB		
	40 ~ 470 MHz	16 dB		
	470 ~ 862 MHz	16 dB		
	862 ~ 1000 MHz	16 dB		
	1000 ~ 1218 MHz	16 dB		
EMC (Class A+10dB)	5 ~ 300 MHz	95 dB		
	300 ~ 470 MHz	90 dB		
	470 ~ 950 MHz	85 dB		
	950 ~ 1218 MHz	65 dB		

Address: No. 27-1, Youyi Road, Guali Town, Xiaoshan District, Hangzhou City, Zhejiang Province.

Company Web Site: [www.prevail-catv.com](http://www.prevail-catv.com)

Sales Line: 0571-82553307

Fax: 0571-82554407