

## DATA SHEET

Item No F-319-N

Connector Type 75 OHM F MALE TERMINATOR

Frequency Range	5 - 1500 MHz
Impedance (Nom.)	75 Ω
Amp. Rating	5 A
Shielding Effectiveness (CoMeT)	> 120 dB @ 30-1000 MHz >110 dB @ 1000-1300 MHz



Return Loss (IEC 169.1.1)  
(RF Analyzer E8357A)

5 - 42 MHz	- 43.7 dB
42 - 70 MHz	- 43.0 dB
70 - 300 MHz	- 41.0 dB
300 - 600 MHz	-38.5 dB
600 - 862 MHz	- 34.5 dB
862 - 1000 MHz	- 32.0 dB
1000 - 1500 MHz	- 29.0 dB

Temperature

Installing	- 5° to + 50° C
Operating	- 40° to + 100° C
Storing	- 40° to + 100° C

Base Material

Body parts	Brass CuZn 39Pb3
Inner conductor	Brass CuZn 39Pb3

Plating

Body parts	Nickel
Inner conductor	Tin

Date of release Aug 03 . 2017

O-ring EPDM

Insulators PE



**BNS PRECISION INDUSTRY CO., LTD**

NO. 2, LANE 166, JIUN YING ST., SHU-LIN CITY, TAIPEI HSIEN, TAIWAN.

Tel: +886 2 26822317

Fax: +886 2 26863077

e-mail: info@bnsco.com.tw

www.bnsco.com.tw