cablesat®
CATV & MICROWAVE

CABLESAT INTERNATIONAL CO., LTD.

DATASHEET

Electrical Information:

Impendance:	75ohm
Bandwidth:	5 to 1218 MHz
Insertion Loss:	1~20dB
Flatness.	± 1 dB
Return Loss:	> 14 dB
Screening Effectiveness:	
5 - 300 MHz	≧ 85 dB
300 - 470 MHz	≧ 80 dB
470 - 950 MHz	≧ 75 dB
950 - 1218 MHz	≧ 55 dB

General Technical Information:

Housing Material:	Brass
Surface treatment:	Nickel Plated
	(Thickness: min 1.5um)
Inner Conductor Material:	Phosphor Bronze
	(Tin Plated)

Interface: F-male to F-Female

cablesat
No. 31, Ln. 2, Sec. 4, Shalian Rd
Dadu Dist., 433 Taichung

Attenuator

Part Number	*Attenuation*
31-ATT01	1 dB
31-ATT02	2 dB
31-ATT03	3 dB
31-ATT04	4 dB
31-ATT05	5 dB
31-ATT06	6 dB
31-ATT07	7 dB
31-ATT08	8 dB
31-ATT09	9 dB
31-ATT10	10 dB
31-ATT11	11 dB
31-ATT12	12 dB
31-ATT13	13 dB
31-ATT14	14 dB
31-ATT15	15 dB
31-ATT16	16 dB
31-ATT17	17 dB
31-ATT18	18 dB
31-ATT19	19 dB
31-ATT20	20 dB