

Item no.

Adapter type

Frequency Range
 Impedance (Nom.)
 Power Rating

Product photo



Transfer Impedance (CoMeT)

 Screening Attenuation(CoMeT)

Return Loss	Better than	Typical
0.3 - 500 MHz	-36 dB	-42,8 dB
500 - 860 MHz	-34 dB	-40,7 dB
860 - 1000 MHz	-32 dB	-39,8 dB
1000 - 1750 MHz	-29 dB	-36,1 dB
1750 - 2150 MHz	-28 dB	-34,4 dB
2150 - 3000 MHz	-26 dB	-31,5 dB

Insertion Loss Max.	Better than	Typical
0.3 - 500 MHz	-	-
500 - 860 MHz	-	-
860 - 1000 MHz	-	-
1000 - 1750 MHz	-	-
1750 - 2150 MHz	-	-
2150 - 3000 MHz	-	-

Temperature
 Installing
 Operating
 Storing

Intermodulation
 3rd Order (@2x100mW)

Inner Conductor Resistance
 (@ 1 A DC)

Sealing Test
 (IEC IP-code)

Insulation Resistance
 (@ 500 VDC)

O-rings

Dielectric Strength
 DC Test Voltage

Base Material
 Body Parts
 Inner Conductor

Max. Tensile Strength
 Overall

Plating
 Body Parts
 Inner Conductor

Torsional Strength
 (Connector / Cable)

Insulators

Test performed by
 Date of release

Remarks

*All tests performed using instruments calibrated in accordance to our ISO 9001 certification.
 Further technical specifications and installation instructions can be obtained on request.*