

FIBER OPTICAL DOME TYPE

www.fcttech.com

Fiber Optical Splice Closure

Description

DOME type fiber optic splice closure is also called as vertical closure, it is suitable for FTTH accessing. The input and output are on the same side. An oval hole and four round holes facilitates the operation. It is suitable for aerial, underground, conduct installation.

Features

- Heat shrinkable sealing structure.
- High quality industrial plastic body material.
- One oval hole and four round holes for cable entrance.
- Suitable for cable diameter 5mm–38mm. .
- Support aerial, underground, pipeline, man holes, hand holes
- Protection level reaches IP68.
- 360 degrees access, fiber bending > 40mm.
- Maximum capacity: 288F single or 864F ribbon.
- Number of trays: 6 pcs x 48F.



Configuration

| Material | Field Size | Max Capacity | | Cable Entrance | Weight | Color |
|----------------------------|----------------------|--------------------------|----------------|---------------------------------|--------|-------|
| Strengthen Polymer Plastic | H*D(mm) 522 * 211 | Splice Cores 96 cores | Trays 6x24F | 2 x oval port 4 x round port | 3.6kg | Black |

Application

- Aerial cable installation
- Pole mounted installation
- Wall mounted installation
- Man hole and hand hole installation
- FTTH access layer

| | | |
|--------------------------------------|------------|-----------------|
| Fiber Optik Kablo Ek Kutusu (12Port) | TKS-FOM-20 | FCF/T-SDC12P.EK |
| Fiber Optik Kablo Ek Kutusu (24Port) | TKS-FOM-21 | FCF/T-SDC24P.EK |
| Fiber Optik Kablo Ek Kutusu (48Port) | TKS-FOM-22 | FCF/T-SDC48P.EK |
| Fiber Optik Kablo Ek Kutusu (96Port) | TKS-FOM-23 | FCF/T-SDC96P.EK |
| FİBER OPTİK KABLO EK KUTUSU (72PORT) | TKS-FOM-46 | FCF/T-SDC72P.EK |

Standard Accessories

Installation bolts and nuts, Protection sleeves, Cable entry rubber, Cable tube.

Optional Accessories

Bracket for wall, pole, pressure valve...etc.