

PRODUCT SPECIFICATION

GALVANIC ISOLATOR (PRIS-101TG)

TKS-RFP-19 HT/PRIS-101TG GALVANİK İZOLATÖR 5-1218 MHz

GENERAL SPECIFICATION



GALVANİK İZOLATÖR-GALVANIC ISOLATOR

	MHz	GI
Geçiş Kaybı iki yönlü-Insertion Loss Two way (Max.) dB	15-1218	1,2
Geri Dönüş Kaybı-Return Loss (In-Out Min.) dB.	15-1218	14
Ekranlama Faktörü-Screening effectiveness EN 50083/2	3-300	85 dB.
	300-470	80 dB.
	470-950	75 dB.
	950-1000	55 dB.

Galvanic Isolation-Galvanik İzolasyon-60 saniye (60 seconds)	2120 V DC / 0,7 mA 230 V AC / 2 mA
Empedans-Impedance	75 ohm
DC Blok-Blocking Capacitors	All Ports
Konnektör-Connector	F-Male
Gövde-Housing	Min. 1.5 mm White Bronze/NiSn/Nickel/Sn/CuSn plated
İç İletken-Center conductor	Gold/Silver/Tin/CuSn/NiSn plated beryllium copper / phosphorus bronze