

HANSEN/RG6TCU 0,25MT-1MT-3MT-5MT-10MT

TKS-KON-19-20-21-22-23 JUMPER KABLO

## GENERAL SPECIFICATION



Cable Family	RG6T
Interface Connector A	F Male Compression Type Nickel-Tin
Interface Connector B	F Male Compression Type Nickel-Tin
Connector Type	Screw type
Operational Environment	Indoor

## ELECTRICAL PROPERTIES

<b>Impedance</b>	75±3 Ω	
<b>Insulation Resistance</b>	≥5000 MΩ•km	
<b>Insertion Loss</b>		
0.25 m	5-1218 MHz	≤0.5 dB
1 m	5-1218 MHz	≤0.9 dB
3 m	5-1218 MHz	≤1.4 dB
5 m	5-1218 MHz	≤1.9 dB
10 m	5-1218 MHz	≤3.1 dB
<b>Return Loss</b>	5-1218 MHz	16
<b>Transfer Impedance</b>	12-30 MHz	2.5 mΩ/m
<b>Screening Attenuation</b>	30-1000 MHz	≥105 dB
	1000-1218 MHz	≥95 dB

## MECHANICAL PROPERTIES

<b>Single Bending Radius</b>	≥35mm
------------------------------	-------

BLUETEL TELEKOMÜNİKASYON VE ENERJİ SİSTEMLERİ SAN. TİC. A.Ş