

PRODUCT SPECIFICATION

TV-SAT COMBINER

TKS-RFP-24 DFU8695 TV-UYDU BİRLEŞTİRİCİ

GENERAL SPECIFICATION



TV UYDU BİRLEŞTİRİCİ (TV-SAT COMBINER)

	PORTLAR	Frekans Aralığı	Özellikler
Maximum Geçiş Kaybı -Insertion Loss dB	IN-ANT	15-860 Mhz	2,5 dB Max.
		950-2150 Mhz	30 dB Min.
	IN-SAT	15-860 Mhz	25 dB Min.
		950-2150 Mhz	2,5 dB Max.
Geri Dönüş Kaybı-Return Loss dB.	ANT	15-860 Mhz	10 dB Min.
	SAT	950-2150 Mhz	8 dB Min.
İzolasyon-Isolation dB.	ANT-SAT	15-860 Mhz	30 dB Min.
		950-2150 Mhz	30 dB Min.
Ekranlama Faktörü-Screening effectiveness EN 50083/2	5-300		85 dB.
	300-470		80 dB.
	470-950		75 dB.
	950-1218		55 dB.

Çalışma Frekans Aralığı- Frequency Range	15-2150 Mhz ANT (15-860) SAT (950-2150) Mhz
Empedans-Impedance	75 ohm
DC Blok-Blocking Capacitors (Low Band)-ANT	50 VDC
Konnektör-Connector	F-Female
Gövde-Housing	Min. 1.5 mm CuSn plated
İç İletken-Center conductor	Gold
Power Pasing-SAT	24 VDC min.- 1 Amper maks.



BLUETEL TELEKOMÜNİKASYON VE ENERJİ SİSTEMLERİ SAN. TİC. A.Ş

ESENTEPE MAH. MİLANGAZ CD. NO:77 DUMANKAYA VİZYON A2 BLOK KAT 32 D:220 KARTAL- İSTANBUL
TEL:(216)5102420 FAX:(216)5102421 info@bluetel.com.tr www.bluetel.com.tr